

linea riga.



Graetz

GR32E9000
32" HD LED TV 12V

MODEL NAME

8053288530419

EAN

MAINBOARD	18AT026	
PANEL	Panel Type	32" LED
	Brightness	270 cd m2 (Typ.)
	Resolution Aspect	1366 x 768 16:9
	Contrast	3000:1
	Viewing Angle	178°
	Screen Size	32" 80,04 cm (diagonal)
	Color	16,7 M
OPERATING SYSTEM	N/A	
POWER SUPPLY	INPUT: 100-240V ~ 50/60Hz, OUTPUT: 12V 4A	
OTHER	Response Time	6.5 MS
	VESA	100 x 100 mm
ACCESSORIES	User Manual Remote Control 2 x Batteries (AAA) Base Stand Screws 2 x M4x15 YSB - 2 x M5x16 YSB	
ENERGY EFFICIENCY	F	
SIZE	Packaging	1 x 800 x 128 x 520 MM
	Product (L x W x H)	732 x 87,2 x 435 MM (without stand) 732 x 205,9 x 483,8 MM (with stand)
WEIGHT	Unit Weight	3,6 KG (net) 4,9 KG (gross)
PRODUCTION	OCT-2020 (First Production)	

TV SYSTEM	ATV	Video & Sound : PAL SECAM , BG DK I L NICAM/A2
		Receiving Range: 48.25MHz ~ 863.25MHz
		Max Storage Channels: 100
	DVB - C	Modulation - QPSK:16QAM,64QAM,32QAM,128QAM, 256QAM
		Receive Channel: 500
DVB - T	Modulation - COFDM 2K/8K, QPSK,16QAM,64QAM	
	Receive Channel: 500	
DVB - T2	Modulation - Compliant with EN302755V1.3.1 COFDM: 1K to 32k; SupportT2-Lite, code rate:1/3,2/5;QPSK:16QAM,64QAM,256QAM Bandwidth:6,7,8Mhz; Guard Interval:1/128-1/4;Code rate: 1/2,3/5,2/3,3/4,4/5,5/6SPP: PP1 to PP8	
	Audio&Video System: MPEG1/2 Layer and II, AC-3, DD/DD+(Option& need license) MPEG-2MP@ML,MPEG-2 MP@HL,H.264,H.265	
DVB - S S2	Modulation - COFDM 2K/8K, QPSK,8PSK	
	LBN Power & Switch Control- Auto/13V/18V/OFF Out put 350mA@Max; 22KHz	
	Receive Channel: 4000	
		DiSEqC 1.0 / 1.1 compatible
VIDEO SYSTEM	MPEG-2MP@ML,MPEG-2 MP@HL,H.264, H.265	
AUDIO SYSTEM	MPEG1/2 Layer and II, AC-3, DD/DD+(Option& need license)	
VIDEO INPUT	HDMI & Component: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p SCART: CVBS & RGB System: PAL/NTSC/SECAM; LEVEL: 1.0 V.±5%	
AUDIO INPUT	AV/Component Audio : Mini RCA Input 0.2 ~ 2.0 VRMS	
AUDIO OUTPUT	Frequency Response: 100Hz~15KHz @±3dB (1KHz, 0dB reference signal) Max Output Power: 2x6W(8Ω) THD+N<10%@1KHz Loudspeaker - 2x8mW (32Ω) THD+N<10%@1KHz Headphone	
POWER CONSUMPTION	TV ON (SDR Mode)	29 W
	STANDBY	0,45 W
BASIC FUNCTION	Parental Control Teletext Hotel Mode (Optional) Subtitle Lock EPG Clock & Timers Sleep Timer Auto Stand-by CI Audio Language Auto Volume Noise Reduction Dynamic Backlight Weak Signal Enhancement	
TERMINALS	INPUT	12V DC Input: 1 x DC Power Socket
		DTV & ATV (Optional): 1 x IEC- connector
		Satellite TV (Optional): 1 x F-Connector
		USB: 1 x USB
		HDMI: 2 x HDMI connectors
		Component / AV Audio & Video: 1 x Mini RCA (Black) 1 x Mini RCA (Black)
	OUTPUT	Scart: 1 x SCART Connector (Black)
		CI Slot (Optional): 1 x CI Slot (Black)
		Headphone: 1 x Mini RCA Connector (Black)
		SPDIF: 1 x Optical
PICTURE	Color Temperature	Cold Normal Warm
	Picture Mode	User (Custom) Standard Dynamic Natural
OSD LANGUAGE	Albanian Arabic Bosnian Bulgarian Croatian Czech Danish Dutch English French German Greek Hungarian Italian Kurdish Latvian Lithuanian Macedonian Norwegian Persian Polish Portuguese Romanian Russian Serbian Slovak Slovene Spanish Swedish Turkish	
MICRO INNOVATION	Multi-Language Schedule List (EPG)	